



- ✓ Active PFC
- ✓ CEC Efficiency Regulations Compliance
- ✓ RoHS Compliance
- ✓ IEC320 C6 (3PIN)
- ✓ Over Voltage Protective Installation
- ✓ Over Current Protective Installation
- ✓ Protection Type: Auto-Recovery
- ✓ Application: Set-Top box, POS, LCD, Printer, IT, Scanner, NB

Specification

Parametry	EA11002A
Output Voltage	12V
Output Rating (Max.)	120W
Output Current (Max.)	10A
Input Voltage (Limit)	AC 90-264V
Input Frequency	47~63Hz
Line Regulation	1% MAX
Load Regulation	± 5%
Ripple & Noise	2% Max.
Efficiency	85%
Active PFC	Yes
Over Voltage Protection	Yes
Over Current Protection	Yes
Operating Temperature	0~40°C
Storage Temperature	-20~85°C
Class I or Class II	Class I
Safety Standards	UL60950-1, IEC60950-1
Safety/EMC	UL/CUL, FCC, TUV, CE, CB
LED Indication	Yes
Dimension	(L. x W. x H.): 177 x 63,5 x 40 mm
Approx. Weight	450 g
Standard Plug	2,1 / 5.5 mm

120W AC-DC Single Output Desktop Type EA11353 series

